

Coral Solvent For Oil Paint

(T-101)

Product description:

Coral Solvent for oil paint is refined water white petrolatum solvent of moderate volatility with good solvency and controlled evaporation for alkyd based products.

Typical use:

It is suitable for thinning air drying Alkyd based products i.e. Gloss, enamel, Undercoat, Metal Primers, Enamel Wood Finishes, Roofing and Floor Enamel, Eggshell enamels, flat alkyds, luster finish, linseed oil, waxes and polishes etc. It is also used for metal cleaning and clean-up of brushes and equipment after painting.

Colors:

Clear

Product data:

Property	Test/Standard	Description
Solids by volume	Calculated	0%
Flash point		Closed cup: 43°C
Density	Measured	0.76-0.78 kg/l
Grade Point		Low Evaporating Thinner
VOC		100%

Packaging (typical):

- 1L, 5L and 200L

The volume stated is for factory made colors. Note that local variants in pack size and filled volumes can vary due to local regulations.

Storage:

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 30 °C:

Coral solvent for Oil Thinner

6 month(s)

Coral Solvent for Oil Thinner

Surface Preparation:

- Gradually add 10-15% of Coral Solvent for oil thinner is to achieve the desired application viscosity.
 - Clean oil and grease from surfaces to be painted using Coral Standard thinner.
 - Remove impurities such as projecting parts, residual oil, rust etc.
-

Warning:

Coral Solvent for oil thinner is highly flammable solvent and should be used in a well-ventilated area. Vapors may cause flash fire. Do not smoke. Extinguish all flame and others sources of ignition during application and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to archive cross-ventilation. Do not empty into drains. To clean the floor and all objects contaminated by this material use water and detergent.

Keep away from food drink and animal feeding stuffs. If swallowed IMMEDIATELY contact Doctor.

First AID:

If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention.

Health and safety:

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Color variation:

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., application quality and generic type of paint.

Disclaimer:

The information contained herein is to the best of our knowledge, accurate and current and is given in good faith without warranty. Users are deemed to have satisfied themselves independently as to the suitability of our products for their intended purpose. In no event shall insignia be liable for consequent or incidental damage.
