

CORALTINT UNIVERSAL STAINERS

(CUS 1)

Product description:

Type

Coraltint universal stainers is a unique range of water or solvent miscible toners which can readily be mixed with Delux Hi cover white , Delux Super Value emulsion or Coral High gloss enamel white to give a wide range of colors depending on quantity and types of tonner used.

Features and benefits

Painters now have the choice to make their shades with Coraltint do it yourself universal stainers. Twelve easy to mix stainers.

Recommended use

Available for mixing with Coral High gloss, Delux Hi Cover or Delux Super Value emulsion, Delux Vinyl Silk Wash & Wear, Delux Weatherguard and Delux PVA Acrylic Roof to get colors of your choice.

Substrate

Tinted paint can be applied on surfaces like cement, brickwork, plywood, asbestos, etc.

Product data:

Packaging size	50 ml and 100 ml
Colors	Red, Blue, Green, Magenta, Black, Yellow, Violet etc.

Application data:

Mix one or more 50 ml bottles of universal stainer with selected pack of Delux Hi Cover or Delux super value or Coral High gloss or Delux Vinyl Silk Wash & Wear or Delux Weatherguard to get the desired shade depth.

Stir the paint until homogeneous. Stainer mixes readily upon stirring.

Apply paint by brush or roller after mixing.

Film thickness per coat

Typical recommended range

Theoretical Coverage: For tinted paint 8-10 m²/ liter

Film thickness will vary and is calculated as average.

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.

Coraltint Universal Stainers

Thinner

Water for cleaning

Dilution

Not Recommended

Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

The drying time is measured by stated values	Relative Humidity (RH) 50 %
Substrate temperature	30 °C
Surface (touch) dry	2 hrs.
Hard dry	4 hrs.
Dry to over coat, minimum	3-4 hrs.

Directions for use:

Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

Recommended paint system (Tinted Paint)

Primer

Coral Alkali Resisting Primer (WB): 1 Coat

Putty

Coral Wall Plaster: 1 Coat

Primer

Coral Alkali Resisting Primer (WB): 1 Coat

Topcoat

All Coral Emulsions Paint : 2 -3 Coats (Depending on Shade)

First coat and second coat as per recommendation on the product label.

Coraltint Universal Stainers

Remarks:

Other systems may be specified, depending on area of use.

Masking tape has to be removed immediately after application of the topcoat.

Contents of packaging with different batch numbers must be mixed together before use. .

Storage:

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Environmental labelling:

Insignia Limited is an ISO 9001 and 14001 certified company for QMS and EMS respectively.

Refer to the product safety data sheet for more information.

Health and safety:

Ensure good ventilation during application and drying. Observe hygiene and safety regulations. Wash your hands carefully after painting. Avoid contact of paint with eyes and skin. Keep out of the reach of children. Do not use can/container to store food and water. Refer to Material Safety Data Sheet for additional safety information.

Disclaimer:

The information contained herein is to the best of our knowledge, accurate and current and is given in good faith without warranty. Users are deemed to have satisfied themselves independently as to the suitability of our products for their intended purpose. In no event shall insignia be liable for consequent or incidental damage.