

## DELUX WASH & WEAR VINYL SILK

(CWB 5)

### Product description:

#### Type

Coral Delux Silk Vinyl is premium high quality Interior Emulsion paint with a fashionable silky finish.

#### Features and benefits

It is extremely tough and easily washable. Delux Vinyl silk is a low odour, low VOC product for interior application with Insignia eco-friendly logo.

#### Recommended use

Recommended for use in hospitals, food processing areas, etc. In addition to plaster, stone, etc. Delux Silk vinyl can be used on timber and is particularly suitable for wallboards/ partitioning, etc. Delux Silk Vinyl has antifungal quality, which is recommended in coastal and tropical/high humidity areas to combat mold growth, algae, etc.

#### Substrate

It can be applied on surfaces like cement, brickwork, plywood, asbestos, etc.

### Product data:

<b>Packaging size</b>	4L, 10L and 20L
<b>Colors</b>	White and As per Coral Shade Card/Fandeck.
<b>Finish, Dry Film</b>	Smooth (Glossy/Matt)
<b>Specific gravity</b>	1.18 ± 0.05
<b>Viscosity</b>	90 -100 KU
<b>Solids by volume</b>	40 ± 2 volume (Theoretical)
<b>VOC Level</b>	Below 12g/L for white, pastel and medium colors. Green seal standard is 50g/L for flat Coatings.
<b>VOC comments</b>	This is the theoretical value. Tested value will vary depending on test methodology, accuracy of equipment used for testing and test conditions.

### Application data:

#### The product can be applied by

**Brush, Roller, Spray** : Recommended.

Brush Recommended to paint corners and edges.

#### Film thickness per coat

#### Typical recommended range

Theoretical Coverage: 8-10 m<sup>2</sup>/ liter

Film thickness will vary and is calculated as average.

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.

## *Delux Wash & Wear Vinyl Silk Emulsion*

### Thinner

Water

### Dilution

Maximum 10 %

### Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

### Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

<b>The drying time is measured by stated values</b>	Relative Humidity (RH) 50 %
<b>Substrate temperature</b>	30 °C
<b>Surface (touch) dry</b>	2 hrs.
<b>Hard dry</b>	4 hrs.
<b>Dry to over coat, minimum</b>	3-4 hrs.

## Directions for use:

### Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

### Recommended paint system

#### Primer

Coral Alkali Resisting Primer (WB): 1 Coat

#### Putty

Coral Wall Plaster: 1 Coat

#### Primer

Coral Alkali Resisting Primer (WB): 1 Coat

#### Topcoat

All Coral Wash & Wear Vinyl Silk Emulsions: 2 -3 Coats (Depending on Shade)

First coat and second coat as per recommendation on the product label.

## *Delux Wash & Wear Vinyl Silk Emulsion*

---

### **Remarks:**

Other systems may be specified, depending on area of use.

Masking tape has to be removed immediately after application of the topcoat.

Contents of packaging with different batch numbers must be mixed together before use. .

---

### **Storage:**

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

---

### **Environmental labelling:**

Insignia Limited is an ISO 9001 and 14001 certified company for QMS and EMS respectively.

Refer to the product safety data sheet for more information.

---

### **Health and safety:**

Ensure good ventilation during application and drying. Observe hygiene and safety regulations. Wash your hands carefully after painting. Avoid contact of paint with eyes and skin. Keep out of the reach of children. Do not use can/container to store food and water. Refer to Material Safety Data Sheet for additional safety information.

---

### **Disclaimer:**

The information contained herein is to the best of our knowledge, accurate and current and is given in good faith without warranty. Users are deemed to have satisfied themselves independently as to the suitability of our products for their intended purpose. In no event shall insignia be liable for consequent or incidental damage.